

# EMERGENCY LIGHTING AND ORIENTATION SYSTEMS

ARSEL 

## VERSALITE LED EMERGENCY LIGHTING FIXTURE



- Wall mount, metal sheet case
- High-intensity emergency lighting
- LED lamp lighting
- Heat-resistant transparent polycarbonate lens
- DALI compatible models

- Versalite ledli emergency luminaire can be used as fixed and mobile.
- Spotlights illuminated fixture is activated only when the power fails.
- There are LEDs on the device indicating the presence of mains voltage and the status of the charge.
- On the device, there is a test button.
- Plug-in type power supply cable is included.
- The charger in the product is designed so that the battery will not be damaged in case of continuous charging.
- 2x26 LED model, 2x50W halogen bulb emits equivalent light. (Lumen level 2x1000)
- The mains supply voltage is standard 220 volts AC 50 Hz.
- Charging time for first use is 24 hours.
- It can withstand fluctuations up to 285 volts at mains voltage.
- Switches to emergency lighting mode under 150 volts, charging over 185 volts.
- It is manufactured according to TS 8710 EN60598-2-22 standard in the framework of ISO 9001-2000 quality management system.

### USAGE AREAS

- Long corridors
- Stairwells
- Indoor Car Parks
- Factories
- Boiler rooms
- Refuges
- Warehouses

### LAMP OPTIONS

- LED 6500°K
- 14-18-26 LED lamp models

### BODY STRUCTURE

- Body - Electrostatic powder gray painted steel case
- Spot - Transparent polycarbonate glazed ABS plastic case, articulated spotlight
- Battery - Dry Type Maintenance-free Battery
- Reflektör - Spot chrome coating reflector
- Carrying handle - Aluminum, painted black

### OPTIONS

- Emergency mode only.
- 1-2-3 hour emergency backup times
- Optional mounting stand



## DEKOLITE Z30 SERIES DOUBLE FACED CEILING MOUNT

MODEL CODE	LIGHTING STYLE	MOUNTING STYLE	LAMP	LIGHT FACE	DURATION (minute)	DIMENSIONS (W-L-H)mm	WEIGHT	IP CLASS	ISOLATION CLASS	OPERATION TEMP	POWER CONSUMPTION	OPERATING VOLTAGE
------------	----------------	----------------	------	------------	-------------------	----------------------	--------	----------	-----------------	----------------	-------------------	-------------------

### VERSALITE LED

MODEL KODU	YANMA DURUMU	MONTAJ ŞEKLİ	LAMBA	İŞIKLI YÜZEY	SÜRE	BOYUTLAR (EN-BOY-YÜKSEKLİK)	AĞIRLIK	IP SINIFI	İZOLASYON SINIFI	ÇALIŞMA SICAKLIĞI	GÜÇ TÜKETİMİ	ÇALIŞMA VOLTAJI
VSL-214-1	Kesintide Yanan	Duvara Montaj	2x14 led	Hareketli Spotlar	Kesintide 60 dak.	85x340x345mm	3,28kg	40	I	-16/+45°	5w	220-240
VSL-214-3	Kesintide Yanan	Duvara Montaj	2x14 led	Hareketli Spotlar	Kesintide 180 dak.	85x340x345mm	3,63kg	40	I	-16/+45°	5w	220-240
VSL-218-1	Kesintide Yanan	Duvara Montaj	2x18 Led	Hareketli Spotlar	Kesintide 60 dak.	85x340x345mm	3,63kg	40	I	-16/+45°	5w	220-240
VSL-218-3	Kesintide Yanan	Duvara Montaj	2x18 Led	Hareketli Spotlar	Kesintide 180 dak.	85x340x345mm	3,85kg	40	I	-16/+45°	5w	220-240
VSL-226-1	Kesintide Yanan	Duvara Montaj	2x26 Led	Hareketli Spotlar	Kesintide 60 dak.	85x340x345mm	3,63kg	40	I	-16/+45°	5w	220-240
VSL-226-3	Kesintide Yanan	Duvara Montaj	2x26 Led	Hareketli Spotlar	Kesintide 180 dak.	85x340x345mm	3,85kg	40	I	-16/+45°	5w	220-240

### VERSALITE LED (DALI uyumlu)

MODEL KODU	YANMA DURUMU	MONTAJ ŞEKLİ	LAMBA	İŞIKLI YÜZEY	SÜRE	BOYUTLAR (EN-BOY-YÜKSEKLİK)	AĞIRLIK	IP SINIFI	İZOLASYON SINIFI	ÇALIŞMA SICAKLIĞI	GÜÇ TÜKETİMİ	ÇALIŞMA VOLTAJI
VSL-226-1 DALI	Kesintide Yanan	Duvara Montaj	2x26 Led	Hareketli Spotlar	Kesintide 60 dak.	85x340x345mm	2,75kg	40	I	-16/+45°	2w	220-240
VSL-226-2 DALI	Kesintide Yanan	Duvara Montaj	2x26 Led	Hareketli Spotlar	Kesintide 120 dak.	85x340x345mm	3,15kg	40	I	-16/+45°	2w	220-240
VSL-226-3 DALI	Kesintide Yanan	Duvara Montaj	2x26 Led	Hareketli Spotlar	Kesintide 180 dak.	85x340x345mm	3,15kg	40	I	-16/+45°	2w	220-240
VSL-226-3 DALI	Kesintide Yanan	Duvara Montaj	2x26 Led	Hareketli Spotlar	Kesintide 180 dak.	85x340x345mm	3,15kg	40	I	-16/+45°	2w	220-240

### ÖLÇÜLER

